IN-LINE PROCESS ANALYZER · OZONE

OZONOTEC ANALYZER

User friendly · waterproof · robust

The process analyzer complements OZONOTEC EC. It continuously measures O_3 concentration and medium temperature in liquid and gas phase. Parameters can be adapted to the measuring conditions and operating requirements. Its stainless-steel, IP65 / NEMA 4X enclosure is designed for continuous process measurements in demanding industrial environments.



OZONOTEC ANALYZER · IP65 STAINLESS

0.01 ppb	IP65	RS 232/485	4-20 mA
RESOLUTION	ENCLOSURE	DIGITAL	ANALOG

Features & Benefits

Easy installation & use

- Process measurements in minutes.
- Quick configuration from function keys and menus on screen.

Real-time display

- Continuous display of the real time concentration and medium temperature.
- Units from 0.01 ppb to 100 ppm dissolved or 1.0 ppm to 100 % gaseous.
- Real time clock · time dependent measurements.

Pin-code protected

- Access levels are protected by a pin-code to prevent uncontrolled modifications of calibration and settings.

Easy sensor calibration

- The sensor calibration process is defined step by step by the software.
- Calibration can be performed with air.

Configuration of alarms

- System alarms can be configured according to specified concentration levels.
- Alarm signals are transmitted through analog outputs.

Waterproof & robust

- Stainless steel construction, IP65 / Nema4X.
- Ideal for measurements in harsh conditions.

Applications

BEVERAGE · SEMICONDUCTOR · PHARMA & CHEMICAL · POWER & STEAM

In-line | Dissolved & gaseous applications | Beverage production | Power-steam industry | Pharmaceutical & chemical industries | Semiconductor industry

Dimensions

WIDTH	HEIGHT	DEPTH	WEIGHT	ENCLOSURE
230 mm	180 mm	75 mm	3.0 kg	IP65 / Nema4X

Technical Specifications

Power	**85-230 VAC, 50/60 Hz**	Range O_3 dissolved	**1 ppb - 50 ppm**
Power consumption	**Max 20 W**	Range O_3 gaseous	**0.5 ppm (v/v) - 100 %**
Operating conditions	**-5 °C to 50 °C**	Dissolved displayed units	**ppm, ppb, mg/l**
Enclosure	**Stainless steel, IP65 / Nema4X**	Dissolved resolution	**0.01 ppb**
Weight	**3.0 kg**	Gaseous displayed units	**%-ppm, kPa**
Dimensions	**230 × 180 × 75 mm**	Gaseous resolution	**0.01 ppm**
Displayed data	**Temperature, measurement, real time clock, membrane type**	Alarm outputs	**High/low or high/high-high relays, resistive load 125 VAC / 20 VDC**
Thermal cut-off	**Factory setting +40 °C / 140 °F, software-adjustable**	Digital outputs	**RS 232 / RS 485**
Calibration	**Single point air and direct calibration**	Analog outputs	**0-20 mA / 4-20 mA**
		Compatible sensor	**OZONOTEC EC**

In Practice

Easy installation & use - the analyzer installs quickly and delivers process measurements within minutes. Its LCD continuously displays real-time concentration and medium temperature, with units from 0.01 ppb to 100 ppm dissolved or 1.0 ppm to 100 % gaseous. On-screen function keys and menus make configuration fast, and a real-time clock timestamps readings.

Alarms & connectivity - system alarms can be configured to specific concentration levels, with signals transmitted through the analog outputs. Digital (RS 232 / RS 485) and analog (0-20 / 4-20 mA) outputs integrate the analyzer into existing control systems. Secure & guided - access levels are protected by a pin-code to prevent uncontrolled changes to calibration and settings. The sensor calibration procedure is defined step by step by the software for repeatable results, and can be performed with air.

Contact
Centec GmbH
Wilhelm-Röntgen-Str. 10 · 63477 Maintal · Germany
Amtsgericht Hanau · HRB 4326
info@centec.de
www.centec.de